

MAXIMUM VERTICAL GRADE (ENGLISH)				
Facility Type	Design Speed (mph)	Maximum Grade (Percent)		
		Flat	Rolling	Mountainous
RURAL				
Minor Collector Roads*	20	7	10	12
	30	7	9	10
	40	7	8	10
	50	6	7	9
	60	5	6	8
	70	4	5	6
Local roads including Residential Collectors and Local Residential Streets*	20	-	11	16
	30	7	10	14
	40	7	9	12
	50	6	8	10
	60	5	6	-
URBAN				
Major Thoroughfares other than Freeway or Expressway	30	8	9	11
	40	7	8	10
	50	6	7	9
	60	5	6	8
Minor Thoroughfares*	20	9	12	14
	30	9	11	12
	40	9	10	12
	50	7	8	10
	60	6	7	9
	70	5	6	7
Local Streets*	20	-	11	16
	30	7	10	14
	40	7	9	12
	50	6	8	10
	60	5	6	-

b. Minimum grade should not be less than 0.5% .

c. Grades for 30 meters (100 ft) each way from intersections (measured from edge of pavement) should not exceed 5%.

* For streets and roads with projected annual average daily traffic less than 250 or short grades less than 150 meters (500 ft) long, grades may be 2% steeper than the values in the above table.

(Reference NCDOT Metric Design Manual page 1-12 T-3)